United States Patent [19]

Fukushima et al.

[11] **Patent Number: 4,680,629**

[45] **Date of Patent: Jul. 14, 1987**

[54] **DISPLAY UNIT**

[75] Inventors: **Nobuo Fukushima, Nagasaki; Shuji Iwata, Hyogo, both of Japan**

[73] Assignee: **Mitsubishi Denki Kabushiki Kaisha, Tokyo, Japan**

[21] Appl. No.: **706,412**

[22] Filed: **Feb. 27, 1985**

[30] **Foreign Application Priority Data**

Feb. 28, 1984 [JP] Japan 59-38313

[51] **Int. Cl.**[4] **H04N 7/087; H04N 7/08**

[52] **U.S. Cl.** **358/147; 358/142; 358/146**

[58] **Field of Search** 358/142, 909, 147, 146, 358/242, 181, 183

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,749,831	7/1973	Simpkins	358/147
4,148,074	4/1979	Stakhov	358/242
4,288,809	9/1981	Yabe	358/147
4,388,639	6/1983	Cox et al.	358/147
4,388,645	6/1983	Cox et al.	358/142

FOREIGN PATENT DOCUMENTS

8203290 9/1986 United Kingdom 358/147

OTHER PUBLICATIONS

The TIFAX XM11 Teletext Decoder; by Bryan Norris & Garry Garrard, pp. 1-19.

Primary Examiner—James J. Groody
Assistant Examiner—Michael D. Parker
Attorney, Agent, or Firm—Sughrue, Mion, Zinn, Macpeak & Seas

[57] **ABSTRACT**

A display unit capable of simultaneously displaying motion pictures, still pictures and character data received in a multiplexed form on a single input terminal. A decoder distributes the motion picture data directly to a motion picture data memory without modification, while a processing device receives the still picture and character data from the decoder and processes it before applying it to a still picture and character data memory. The outputs of the two memories are ORed together, then applied to drive a cathode-ray tube.

1 Claim, 2 Drawing Figures